

PRODUCT SPECIFICATIONS SHEET

Model: Jazzy 600 ES

Document Information: INFINF B3327/Rev A/July 2014

| | |
|------------------------------------|--|
| Class of Use: | B |
| Weight Capacity: | 136 kg/21 stone 6 lbs. (300 lbs.) |
| Maximum Speed: ¹ | Up to 6.4 km/h (4 mph) |
| Ground Clearance: ² | 7 cm (2.75 in.) at battery tray 10.2 cm (4 in.) at motor |
| Turning Radius: ² | 52.1 cm (20.5 in.) with front riggings |
| Overall Size: ^{2, 6} | Length: 102.2 cm (40.25 in.) with front riggings 90.2 cm (35.5 in.) without front riggings Width: 62.2 cm (24.5 in.) |
| Drive Wheels: | 35.56 cm (14 in.) solid |
| Castor Wheels: | Front: 15.24 cm (6 in.) solid Rear: 15.24 cm (6 in.) solid |
| Suspension: | ATX Suspension (Active-Trac® with extra stability) |
| Range: ^{1, 4} | Up to 30 km (18.64 miles) |
| Component Weights: ⁵ | Base: 56.1 kg (123.6 lbs.) Batteries: 16.9 kg (37.2 lbs.) each |
| Drivetrain: | Two motor, Mid-wheel 6® drive |
| Brakes: | "Intelligent Braking" electronic regenerative, disc park brake |
| Batteries: ³ | Two 12-volt, deep-cycle NF-22 batteries |
| Battery Charger: | 8-amp, off-board |
| Maximum Allowable Incline: | 10.5% (6°) |
| Maximum Angle Capacity: | 13.2% (7.5°) |
| Maximum Obstacle Climbing Ability: | 7 cm (2.75 in.) |

¹ Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tyre type and tyre condition. This specification is subject to a variance of +10%, -5%.

² Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.

³ AGM or Gel-Cell type required. See VI. "Batteries and Charging."

⁴ Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

⁶ Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA testing requirements and ISO 7176 Series EN12184 standards. All specifications subject to change without notice.



